

Exacting Standards, Just Like yours, since 1948

Project Item Number Quantity

87138



Features:

- · Heavy Duty, High Volume Slicer
- Easy to use automatic mode with variable speed drive
- Easily switch between auto and manual with a single twist of your wrist.
- Unique drip tray fence redirects liquids away from controls and operator towards distinctive concaved base casting for easy cleaning
- 13" Precision slicing German hollow ground blade
- Ergonomic comfort design operation
- Powerful 1/2 hp motor standard
- Adjustable slice thickness from 0 to 7/8"
- Capable of slicing ample amounts of cheese
- Easily removable sharpener for cleaning
- Quick and simple disassembly of carriage and feed grip for easy and thorough cleaning
- Sanitary polished & anodized aluminum finish
- Carriage easily detaches for ease of washing and sanitizing.

8713S Premium Series Automatic Slicer

8713S: 1/2HP Premium series slicer





Certified by NSF International to Meet and Exceed the NSF/ ANSI 2010 standards

13" Precision slicing German hollow ground blade
Automatic mode with variable speed drive
Unique smooth curve transitions to redirect
liquids away from controls and operator
Powerful 1/2 hp motor standard

- Heavy duty 3-1/2 lb gravity feed grip
- Permanantly mounted protective edge guard
- 3 inch legs make cleaning under slicer a breeze

Optional Accessories:

- Stainless Steel Blade
- Heavy Duty Clear Plastic Cover
- Stainless Steel Vegetable Chute
- · Sturdy Stainless Steel Stand

Warranty:

• 1 year, on-site parts and labor

Warranty Details

The 8713S carries a 1 year, on-site parts and labor warranty against any flaws in materials and workmanship. This period begins on the date of the purchase and, provided the unit is used in accordance with our instructions, is in full effect for 1 year from that date. Any work performed under this warranty must be performed between the hours of 8am and 5pm Monday through Friday. Univex will not pay for overtime charges for work performed other then during normal business hours. Damage incurred in transit or from installation error, accident, alteration or misuse is not covered. Univex shall not be liable for any consequential compensatory, incidental, or special damages. Contact the Univex service department for any warranty claims.




Univex Corporation www.Univexcorp.com

3 Old Rockingham Rd Salem, NH 03079 United States of America Telephone (800) 258-6358 Intl Tel. (603) 8936191 Fax (800) 356-5614 Intl Fax (603) 8931249



8713S Premium Slicer

8713S



Width 22.5" (57.15cm)

Depth 30" (76.2cm)

Height 23.5" (59.69cm)

Auto or Manual	Motor	Volts	Hz	Amps	Drive Type	Blade RPM		Blade Diameter	Max Slice	Produc Rec (Rectangle)	ct Cutting Capad S (Square)	City R (Round)
Manual/ Automatic	1680 RPM 1/2 HP (.37kW)	115V 220V	60 50-60	5.4amp 2.7amp	Gear Driven	300	Medium-High Volume	n 13" (33cm)	.875" (22.2mm)	10" x 6.5" (25.4cm x 16.5cm)	6.5" x 6.5" (16.5cm x 16.5cm)	9″) (22.9cm)

Carriage stroke: Manual:12" (~30cm)

Automatic: 12" (~30cm)

Strokes per minute: Minimum: 21 strokes per minute

Maximum: 47 strokes per minute

Controls: Manual slice thickness knob, push button on/off, Attached blade sharpener, automatic/manual feed cam lever, and adjustable carridge speed control.

NSF International certified ANSI/ NSF 8

This slicer is certified by NSF International to meet and exceed the NSF 8 standard. Here is a list of highlighted features that are standard on our entire ANSI/ NSF8 certified slicer line:

- Improved liquid and food particle diversion from all control surfaces
- Improved seals and gaskets for longer life and greater sanitary standards
- Clear and easy to follow cleaning and sanitizing instructions

Shipping Information:

 Freight Class:
 85

 Net Weight:
 133lbs (60.3kg)

 Shipping Weight:
 142lbs (64.4kg)

Shipping Box Dimensions:

 Height:
 25.2" (640mm)

 Width:
 24.8" (630mm)

 Length:
 32.7" (830mm)









Univex Corporation www.Univexcorp.com

3 Old Rockingham Rd Salem, NH 03079 United States of America Telephone (800) 258-6358 Intl Tel. (603) 8936191 Fax (800) 356-5614 Intl Fax (603) 8931249