

Proje	ect	Item Number			Quantity	
R			Λ	MADE IN THE US	SA	<b>G-PEELER</b>
<b>G-PEELER</b>				Portable Models:	20 lb. Ca	BLE PEELER pacity Peeler Vegetable Peeler
20 Pound Portable Vegetable Peeler		Great for carrots use it to No plur dard fa Univex Stainles and ma Precisio	ortable. Plugs in anyv or root vegetables su and parsnips. Some o clean shellfish and s mbing problems. Con ucet and operates on 150 stand, counter o ss steel construction akes cleaning easy. on timer - automatical I, prevents over-peeli	where. ch as potatoes, customers even scale small fish. nects to a stan- a drain board, r table. insures long life w Ily shuts off as	andard Accessor • Durable peelin • Flexible water • Corrosion resis arranty • one-year, on-si	g disc. inlet hose.
Univex Corporation	The pure war wor	splashi Corrosi Cord au RRANTY D e G-peeler ca chase and, pr ranty must b k performed vex shall not	DETAILS DETAILS DETAILS arries a one-year, on-site parts and ovided the unit is used in accorda e performed between the hours of other than during normal busines	l labor warranty against any flaws in nce with our instructions, is in full e '8:00 a.m. and 5:00 p.m. local time, s hours. Damage incurred in transit	ffect for one year from th Monday through Friday. or from installation error,	hip. This period begins on the date of at date. Any work performed under this Univex will not pay for overtime charges for accident, alteration or misuse is not covered. ivex service department for any warranty
				Corporation vexcorp.com	Telephone (800)	m Rd Salem, NH 03079 USA 258-6358 Fax: (800) 356-5614 3-6191 Int'l Fax: (603) 893-1249



## 20 Ib. VEGETABLE PEELER

# **G-PEELER**



Dimensions: A Height: B Width: C Overall Height:	23 1/2" 15 1/4" 27"	(597mm) (387mm) (686mm)
Shipping Information: Freight Class: Net Weight: Shipping Weight:	85 76 lb. 88 lb.	(34Kg) (40Kg)
Shipping Box Dimensio Height: Width: Length:	ns: 31" 22" 24"	(787mm) (559mm) (610mm)

Capacity:

Up to 20 lb. of potatoes per batch. Maximum capacity can vary based on size and shape of potatoes.

### Motor / Drive:

1/3 HP, 1725 RPM.

#### Electrical:

115V,60HZ,1PH, 6.2 amps, Also available at an additional charge: 208-240V,60HZ,1PH 220-240V,50HZ, 1PH

#### Controls:

Timer switch, 5 minute maximum.

#### Housing:

Stainless Steel.

#### Cover:

Corrosion resistant cover.

#### Discharge:

Extended discharge tube minimizes splashing.

#### Discharge Door:

Easy to lock into place. Sealed against leakage.

#### Water Connection:

Flexible water inlet hose, connects to sink tap.

Printed in the USA

10/09

univex

Univex Corporation www. Univexcorp.com

3 Old Rockingham Rd Salem, NH 03079 USA Telephone (800) 258-6358 Fax: (800) 356-5614 Intl Tel. (603) 893-6191 Int'I Fax: (603) 893-1249