

Project			Item Number	Item Number Quantity		
	Light	Duty Level Medium Hea			MG22	
22		Meat & Food Grinder With #22 Hub				
MG2			Models: MG22: 1H	P Meat Grinde	۶r	
Meat & Food Grinder With #22 Hub				 Standard Accessories 16 X 24" feed pan. Aluminum stomper. #22 3/16" grind plate. #22 X-knife. Optional Accessories 1000726 1/8" grind plate. 1000727 3/16" grind plate. 1000728 1/4" grind plate. 1000729 3/8 grind plate. 1000729 3/8 grind plate. 1000730 1/2" grind plate 1000725 X-knife. 1000733 1/2" stuffing tube. 		
Univex Corporation	Cord a	DETAILS at grinder carries a one-year, on-se , provided the unit is used in acco be performed between the hours of 0 other than during normal busine	Wai	effect for one year from that dat fonday through Friday. Univex from installation error, acciden	& labor warranty anship. This period begins on the date te. Any work performed under this will not pay for overtime charges for t, alteration or misuse is not covered.	
	nīvex		Corporation ivexcorp.com		alem, NH 03079 USA 58 Fax: (800) 356-5614 Int'l Fax: (603) 893-1249	



Exacting Standards, Just Like yours, since 1948

Meat & Food Grinder

MG22



22"	(559mm)					
35"	(889mm)					
21"	(533mm)					
Shipping Information:						
85						
115 lb. (52Kg)						
147 lb. (67Kg)						
Shipping Box Dimensions:						
27" (686mm)						
36" (914	mm)					
23" (584	,					
	35" 21" 85 115 lb. († 147 lb. († 27" (686 36" (914					

Electrical:

115V,60HZ,1PH Also available at no additional charge: 208-240V,60HZ,1PH 220-240V,50HZ, 1PH

Motor:

1 HP cycloidal, grease packed gear motor provides compact, smooth and quiet performance with 8:1 reduction within the gear motor, resulting in a 224 rpmdrive shaft output. Grinding worm is directly driven by the gear motor output shaft.

Drive Assembly:

Completely enclosed in an acrylic urethane silver enamel finished 10 gauge steel housing and a no. 4 finished 20 gauge stainless steel cover.

Switch:

Momentary contact start/stop push button. Contactor provides no voltage release protection preventing accidental start-up in the event of power interruption. Micro switch interlock prevents operation of the unit without the chopper properly mounted.

Cord & Plug:

6ft. (1830mm) long 3-wire, 16 gauge SJTO cord with polarized molded plug. NEMA 5-15P or NEMA 6-15P. Meat Grinder:

Cast aluminum housing, worm and ring. Housing is mounted onto the power base by two threaded studs and tightened on with two knobs. Housing has internal spiral flutes which match flutes in the tapered worm. Flutes are designed to shear and force the product into the hardened steel knife and through the sizing holes of the plate. Designed to accept industry standard #22 plates and knives.

Dimensions:

Feed Pan:

16" X 24" (406 X 610mm) aluminum

Feed Stomper:

Cast aluminum stomper designed for ease of handling and operators safety.

Storage Container:

18 1/2" X 13 1/2" (470 X 343mm) plastic with cover.

Capacity:

25 lbs. (11 kg.) per minute on first grind using a plate with 3/16" (4mm) holes.

Optional Accessories:

The following are available at an extra cost:

1000726 1/8" Grind Plate

1000727 3/16" Grind Plate

1000728 1/4" Grind Plate

1000729 3/8" Grind Plate

1000730 1/2" Grind Plate

1000725 X-knife

1000733 1/2" Stuffing Tube

1000734 3/4" Stuffing Tube

1000452 Cover: Heavy-duty clear plastic cover.

Printed in the USA

10/09



Univex Corporation www. Univexcorp.com

3 Old Rockingham Rd Salem, NH 03079 USA Telephone (800) 258-6358 Fax: (800) 356-5614 Intl Tel. (603) 893-6191 Int'l Fax: (603) 893-1249