

Project	Item Number	Quantity
---------	-------------	----------

Stone Deck Oven



*Shown on optional proofer

Pizza Stone Deck Oven - Electric

Models:

- PSDE Type A:** 1-3 deck oven
- PSDE Type B:** 1-3 deck oven
- PSDE Type C:** 1-3 deck oven
- PSDE Type D:** 1-3 deck oven

Pizza Oven

Features:

- The Univex electric pizza oven is designed for high end baking with high turnover production
- Baking chambers are comprised of sand blasted refractory brick (the entire chamber is comprised of refractory brick)
- The heating elements of each deck are located WITHIN the brick so they heat from within
- Each deck has a SINGLE door, with tempered glass for viewing of product during baking
- Rock wool insulation throughout and special "blade" to trap heat when the door is open

Options:

- Proofing compartment with wheels, height 800 mm(31 1/2")
- Stand with wheels, height 600 mm(23 5/8")
- Stand with wheels, height 800 mm(31 1/2")
- Stand with wheels, height 950 mm(37 3/8")
- Additional tray holder guides for compartment and stand
- Spacer element height 300 mm(11 13/16")



Warranty:

- One year, on-site parts and labor

Univex Corporation

Warranty Details

The oven carries a one year, on-site parts and labor warranty against any flaws in materials and workmanship. This period begins on the date of the purchase and, provided the unit is used in accordance with our instructions, is in full effect for one year from that date. Any work performed under this warranty must be performed between the hours of 8am and 5pm Monday through Friday. Univex will not pay for overtime charges for work performed other than during normal business hours. Damage incurred in transit or from installation error, accident, alteration or misuse is not covered. Univex shall not be liable for any consequential compensatory, incidental, or special damages. Contact the Univex service department for any warranty claims.



Exacting Standards, Just Like yours, since 1948

Stone Deck Pizza Oven

Electric

External Dimensions of Oven Deck only (does not include stand or proofer)

Oven Type	1 Deck (WxDxH)	2 Decks (WxDxH)	3 Decks (WxDxH)
Type A	40.2x65x29.5 inch	40.2x65x45.3 inch	40.2x65x61 inch
Type B	52x53.2x29.5 inch	52x53.2x45.3 inch	52x53.2x61 inch
Type C	52x65x29.5 inch	52x65x45.3 inch	52x65x61 inch
Type D	60x68.1x29.5 inch	60x68.1x45.3 inch	60x68.1x61 inch

Type A information (includes stand/proofer)

Oven Type	Max Weight	Max Height	Baking Capacity (pizza)	Baking Capacity (pans)
Type A 1 deck	772 Lbs (350Kg)	72.9 inches	(6) 12" or (2) 18"	(2) 18x26"
Type A 2 decks	1168 Lbs (530Kg)	88.5 inches	(12) 12" or (4) 18"	(4) 18x26"
Type A 3 decks	1500 Lbs (680Kg)	108.3 inches	(18) 12" or (6) 18"	(6) 18x26"

Type B information (includes stand/proofer)

Oven Type	Max Weight	Max Height	Baking Capacity (pizza)	Baking Capacity (pans)
Type B 1 deck	772 Lbs (350Kg)	72.9 inches	(6) 12" or (2) 18"	(2) 18x26"
Type B 2 decks	1168 Lbs (530Kg)	88.5 inches	(12) 12" or (4) 18"	(4) 18x26"
Type B 3 decks	1500 Lbs (680Kg)	108.3 inches	(18) 12" or (6) 18"	(6) 18x26"

Type C information (includes stand/proofer)

Oven Type	Max Weight	Max Height	Baking Capacity (pizza)	Baking Capacity (pans)
Type C 1 deck	910 Lbs (413Kg)	72.9 inches	(9) 12" or (3) 18"	(2) 18x26"
Type C 2 decks	1351 Lbs (613Kg)	88.5 inches	(18) 12" or (6) 18"	(4) 18x26"
Type C 3 decks	1792 Lbs (813Kg)	108.3 inches	(27) 12" or (9) 18"	(6) 18x26"

Type D information (includes stand/proofer)

Oven Type	Max Weight	Max Height	Baking Capacity (pizza)	Baking Capacity (pans)
Type D 1 deck	914 Lbs (415Kg)	72.9 inches	(12) 12" or (5) 18"	(2) 18x26"
Type D 2 decks	1552 Lbs (704Kg)	88.5 inches	(24) 12" or (10) 18"	(4) 18x26"
Type D 3 decks	2096 Lbs (951Kg)	108.3 inches	(36) 12" or (15) 18"	(6) 18x26"

Amp Draw: Per deck

A deck: @208 volt 21.4 amp @240 volt 18.5 amp
 B deck: @208 volt 21.4 amp @240 volt 18.5 amp
 C deck: @208 volt 29.2 amp @240 volt 25.3 amp
 D deck: @208 volt 38.1 amp @240 volt 33 amp

Internal Dimensions

A deck: 25.6"x 40.6"x 7.0"
 B deck: 37.4"x 28.7"x 7.0"
 C deck: 37.4"x 40.6"x 7.0"
 D deck: 45.2"x 43.7"x 7.0"



Univex Corporation
www.Univexcorp.com

3 Old Rockingham Rd
 Salem, NH 03079
 United States of America

TEL: 800.258.6358
 INTL TEL: 603.893.6191
 FAX: 800.356.5614
 INTL FAX: 603.893.1249