



Univex Corporation www.Univexcorp.com 3 Old Rockingham Rd Salem, NH 03079 United States of America Telephone (800) 258-6358 Intl Tel. (603) 8936191 Fax (800) 356-5614 Intl Fax (603) 8931249



Exacting Standards, Just Like yours, since 1948

		Dimensions:	
	É	SL250RB	SL300RB
univers	A:	52.8" (1343mm)	52.8" (1343mm)
	B:	79.1" (2010mm)	79.1" (2010mm)
	 D C :	89.7" (2281mm)	89.7" (2281mm)
	D:	58.3" (1481mm)	58.3" (1481mm)
	E:	77" (1955mm)	77" (1955mm)
A W A		B: Total mixer w	dth including bowl diame epth
biral:	Shipping In	D: Mixer Height E: Mixer height	with head tipped back
piral: L 250RB : 31HP, 22.75KW	Shipping In Freight Class:	D: Mixer Height E: Mixer height	epth when head fully open with head tipped back SL200RB 85
piral: L 250RB : 31HP, 22.75KW L 300RB : 31HP,22.75KW	Freight Class: Net Weight:	D: Mixer Height E: Mixer height formation: SL160RB 85 2285lb (1038kg)	with head tipped back
Notor: piral: 2250RB: 31HP, 22.75KW 2300RB: 31HP,22.75KW Electrical: 220V/60Hz/3P (Contact factory for alternate voltages ontrols: Control panel with digital timers. Seperate timers for hig and low speed. Security key for manual use. Bowl reve direction switch.	Freight Class: Net Weight:) Shipping Weight gh Shipping B	D: Mixer Height E: Mixer height formation: SL160RB 85 2285lb (1038kg) : 2550lb (1156kg) cx Dimensions RB SL200R	with head tipped back SL200RB 85 2285lb (1038kg) 2550lb (1156kg) B
piral: L250RB: 31HP, 22.75KW L300RB: 31HP,22.75KW Clectrical: 220V/60Hz/3P (Contact factory for alternate voltages ontrols: Control panel with digital timers. Seperate timers for hig and low speed. Security key for manual use. Bowl reve	Freight Class: Net Weight:) Shipping Weight gh Shipping B rse SL160	D: Mixer Height E: Mixer height states and the second seco	with head tipped back SL200RB 85 2285lb (1038kg) 2550lb (1156kg) B am) am)
piral: L250RB: 31HP, 22.75KW L300RB: 31HP,22.75KW Clectrical: 220V/60Hz/3P (Contact factory for alternate voltages ontrols: Control panel with digital timers. Seperate timers for hig and low speed. Security key for manual use. Bowl reve direction switch.	Freight Class: Net Weight: Shipping Weight Shipping B SL160 Height: 70.8"(180 Width: 92.5"(235 Depth: 68.9"(175 Cubic Measure:	D: Mixer Height E: Mixer height states in the ight formation: sL160RB 85 2285lb (1038kg) : 2550lb (1156kg) cx Dimensions RB SL200R 00mm) 70.8"(1800n 50mm) 92.5"(2350n	sL200RB 85 2285lb (1038kg) 2550lb (1156kg) B nm) nm)

Unive

Univex Corporation www.Univexcorp.com

3 Old Rockingham Rd Salem, NH 03079 United States of America Telephone (800) 258-6358 Intl Tel. (603) 8936191 Fax (800) 356-5614 Intl Fax (603) 8931249