

UNDERCOUNTER SIDE-MOUNT FREEZERS

VUF67

- Equipped with Secure-Temp 1.0™ Technology™
- 3 Year Parts & Labor Warranty Plus an Additional 2 Year Compressor Warranty
- Exclusive 2 Year Warranty on Santoprene Door Gaskets

VICTORY ULTRASPEC™
FEATURING: **SecureTemp™**
1.0

Secure-Temp 1.0™ is the industry's first and only full service temperature monitoring solution for your kitchen. Secure-Temp 1.0™ is standard on all Victory models and is HACCP compliant & meets NAFEM's data protocol.

There are NO software or monthly monitoring fees.
Optional add on kits are available for additional units.

STANDARD FEATURES

- Expansion Valve Technology
- Full Electronic Control
- High Performance, Balanced, Bottom-Mounted Refrigeration
- Anti-Corrosion Coated Evaporator Coil
- Stainless Steel Exterior / Stainless Steel Interior
- Cabinet back and bottom galvanized steel
- Environmentally Safe R404 Refrigerant For Freezers
- 2" Thick Foamed-in-Place Polyurethane Insulation
- Self-Closing Door(s) with 120° Hold Open Feature
- 2 Epoxy Coated Shelves
- 6" Casters Standard, 2 with Brakes
- Cartridge Style Hinges
- 10' Cord and Plug (see electrical data for details)

Image Coming Soon

VUF67

OPTIONS & ACCESSORIES

- Change Door Swing
- 220/50 Hz, 220/60Hz Voltages
- 3" Overall Height Casters (Set of 4)
- Extra Shelves



Please refer to www.energystar.gov to view the most up-to-date product listing and performance data

3779 Champion Blvd—Winston-Salem, NC 27105

PH: (888) 845-9800 - Fax: (800) 253-5168

sales@victoryrefrigeration.com www.victoryrefrigeration.com

CABINET CONSTRUCTION

Heavy duty construction includes exterior stainless steel on front, sides, doors and grille. Cabinet back and bottom are galvanized steel. Interior liner is made of corrosion resistant aluminum. Interior thermometer is standard.

Cabinet is insulated with 2" thick foamed-in-place polyurethane insulation. Sub-top insulated with 1-1/2" foamed-in-place polyurethane insulation. Doors are mounted to cabinet on self-closing, cartridge style hinges with 120° stay open feature. Doors are equipped with a snap-in-place vinyl magnetic gasket for positive seal. 6" high casters are standard, 2 include brakes. An 8' cord set is provided with 115 volt models. Cabinet interior standard with 2 steel wire epoxy coated shelves per section.

ELECTRONIC CONTROL

REFRIGERATION SYSTEM

Forced air refrigeration systems use expansion valve to meter refrigerant. Automatic electric defrost is standard. Automatic (non-electric) condensate evaporator is provided.

Freezer maintains product temperatures at 0°F and below.

CHARACTERISTICS	VUF67
Net Capacity (cu. ft.)	19.2
Width, Overall (in.)	67"
Depth, Overall (less handles)	33 7/8"
Depth, Door(s) Open 90° (in.)	57"
Height Overall	34 5/8"
No. Full/Half Doors	2F
No. of Shelves	4

ELECTICAL DATA

Condensing Unit Voltage	115/60/1
Total Amperes	8.6

NOTE: Plug style, voltage and full load amps may vary depending on certain options selected such as optional voltages and compressor upgrades.

REFRIGERATION DATA

Condensing Unit Size	3/4 HP
Refrigerant	R-404A

CRATED WEIGHT	397 LBS
----------------------	---------

* Remote units use R-404A refrigerant standard and come with 6" legs

