

## UNDERCOUNTER REFRIGERATORS

VUR36

- Equipped with Secure-Temp 1.0™ Technology™
- 3 Year Parts & Labor Warranty Plus an Additional 2 Year Compressor Warranty
- Exclusive 2 Year Warranty on Santoprene Door Gaskets

**VICTORY ULTRASPEC™**  
FEATURING: **SecureTemp™**  
1.0

Secure-Temp 1.0™ is the industry's first and only full service temperature monitoring solution for your kitchen. Secure-Temp 1.0™ is standard on all Victory models and is HACCP compliant & meets NAFEM's data protocol.

There are NO software or monthly monitoring fees.  
Optional add on kits are available for additional units.

### STANDARD FEATURES

- Expansion Valve Technology
- Full Electronic Control
- High Performance, Balanced, Bottom-Mounted Refrigeration
- Anti-Corrosion Coated Evaporator Coil
- Stainless Steel Front, Sides, Door, & Grill
- Interior liner is made of corrosion resistant aluminum
- Cabinet back and bottom galvanized steel
- Environmentally Safe R134A Refrigerant For Refrigerators
- 2" Thick Foamed-in-Place Polyurethane Insulation
- Self-Closing Door(s) with 120° Hold Open Feature
- 4 White Epoxy Coated Shelves
- 6" Casters Standard, 2 with Brakes
- Cartridge Style Hinges
- 10' Cord and Plug (see electrical data for details)

**Image Coming Soon**  
**VUR36**

### OPTIONS & ACCESSORIES

- Change Door Swing
- 220/50 Hz, 220/60Hz Voltages
- 3" Overall Height Casters (Set of 4)
- Extra Shelves



Please refer to [www.enr.com](http://www.enr.com) to view the most up-to-date product listing and performance data

3779 Champion Blvd—Winston-Salem, NC 27105  
PH: (888) 845-9800 - Fax: (800) 253-5168  
sales@victoryrefrigeration.com www.victoryrefrigeration.com

**CABINET CONSTRUCTION**

Heavy duty construction includes stainless steel on front, sides, doors and grille. Stainless steel 2 1/2" thick worktop with 4" high removable backsplash. Cabinet back and bottom are galvanized steel. Interior liner is made of aluminum for longer lasting corrosion protection. Interior thermometer is standard.

Cabinet is insulated with foamed-in-place polyurethane insulation of 2" minimum thickness. Doors are mounted to cabinet on self-closing, cartridge style hinges with 120° stay open feature. A plug-in type vinyl magnetic gasket is attached to each door for positive seal. Convenient, contoured, pull handle is made of black anodized aluminum. Interior arrangement includes 2 steel wire epoxy coated shelves behind each door, adjustable in 1/2 inch increments.

**ELECTRONIC CONTROL**

**REFRIGERATION SYSTEM**

Refrigeration system utilizes R134a refrigerant metered by expansion valve. Automatic (non-electric) condensate evaporator is standard. Interior forced air system, with high humidity evaporator coils, provides the ideal environment for food preservation.

Refrigerators operate at 36°- 38°F

CHARACTERISTICS	VUR36
Net Capacity	8.5
Width, Overall (in.)	36"
Depth, Overall	32 3/4"
Depth, Door(s) Open 90°	62 1/4"
Height Overall	39 5/8"
No. Full/Half Doors	2F
No. of Shelves	4

**ELECTICAL DATA**

Condensing Unit Voltage	115/60/1
Total Amperes	3.3

**NOTE:** Plug style, voltage and full load amps may vary depending on certain options selected such as optional voltages and compressor upgrades.

**REFRIGERATION DATA**

Condensing Unit Size	1/5 HP
Refrigerant	R-134A

<b>CRATED WEIGHT</b>	210 LBS
----------------------	---------

\* Remote units use R-404A refrigerant standard and come with 6" legs

