

## UNDERCOUNTER REFRIGERATORS WITH DRAWERS

VURD27-2

- Equipped with Secure-Temp 1.0™ Technology™
- 3 Year Parts & Labor Warranty Plus an Additional 2 Year Compressor Warranty
- Exclusive 2 Year Warranty on Santoprene Door Gaskets

**VICTORY ULTRASPEC™**  
FEATURING: **SecureTemp™**  
1.0

Secure-Temp 1.0™ is the industry's first and only full service temperature monitoring solution for your kitchen. Secure-Temp 1.0™ is standard on all Victory models and is HACCP compliant & meets NAFEM's data protocol.

**There are NO software or monthly monitoring fees.**  
Optional add on kits are available for additional units.

### STANDARD FEATURES

- Secure-Temp 1.0™ Technology
- Expansion Valve Technology
- Full Electronic Control
- High Performance, Balanced, Bottom-Mounted Refrigeration
- Anti-Corrosion Coated Evaporator Coil
- Stainless Steel Front, Sides, Drawers, & Grill
- Interior liner is made of corrosion resistant aluminum
- Cabinet back and bottom galvanized steel
- Environmentally Safe R134A Refrigerant For Freezers
- 2" Thick Foamed-in-Place Polyurethane Insulation
- Santoprene Door Gaskets with Exclusive 2 Year Warranty
- Telescoping drawers slides
- Slides include locking mechanism to prevent drawers from being pulled off of cabinets
- Upper drawers accommodates 6" deep foodservice pans (*pans not included*)
- Lower drawers accommodates 4" deep foodservice pans (*pans not included*)
- 6" Casters Standard, 2 with Brakes
- 10' Cord and Plug (see electrical data for details)

**Image Coming Soon**  
**VURD27-2**

### OPTIONS & ACCESSORIES

- Change Door Swing
- 3" Overall Height Casters (Set of 4)
- Stainless Steel Interior
- 220/50Hz, 220/60Hz Voltages



Please refer to [www.victoryref.com](http://www.victoryref.com) to view the most up-to-date product listing and performance data

3779 Champion Blvd—Winston-Salem, NC 27105

PH: (888) 845-9800 - Fax: (800) 253-5168

sales@victoryrefrigeration.com www.victoryrefrigeration.com

**CABINET CONSTRUCTION**

Heavy duty construction includes exterior stainless steel on front, sides, drawers and grille. Cabinet back and bottom are galvanized steel. Interior liner is made of corrosion resistant aluminum. Interior thermometer is standard.

Cabinet is insulated with 2" thick foamed-in-place polyurethane insulation. Sub-top insulated with 1-1/2" foamed-in-place polyurethane insulation. 6" high casters are standard, 2 include brakes. An 8' cord set is provided with 115 volt models.

**DRAWER CONSTRUCTION**

Drawer frames are constructed of heavy-duty stainless steel and are supported on heavy-duty telescoping drawer slides for maximum support of stored food products. Slides have locking mechanism to prevent from drawers being pulled off of cabinets. Upper pull-out drawers accommodate 6" deep pans. Lower pull-out drawers accommodate two 4" deep pans. Heavy-duty pan divider supports are supplied. Foodservice pans for drawers are not included. Snap-type vinyl magnetic gasket is attached to each drawer for positive seal.

**ELECTRONIC CONTROL**

**REFRIGERATION SYSTEM**

Forced air refrigeration systems use expansion valve to meter refrigerant. Automatic electric defrost is standard. Automatic (non-electric) condensate evaporator is provided.

Refrigerators operate at 36°- 38°F

CHARACTERISTICS	VURD27-2
Net Capacity (cu. ft.)	7.3
Width, Overall (in.)	27"
Depth, Overall (less handles)	29"
Depth, Drawers Open	42 7/8"
Height Overall	34 5/8"
No. Doors/Drawers	2
No. of Shelves	-

**ELECTICAL DATA**

Condensing Unit Voltage	115/60/1
Total Amperes	4.0

**NOTE:** Plug style, voltage and full load amps may vary depending on certain options selected such as optional voltages and compressor upgrades.

**REFRIGERATION DATA**

Condensing Unit Size	1/6 HP
Refrigerant	R-134A

<b>CRATED WEIGHT</b>	157 LBS
----------------------	---------

\* Remote units use R-404A refrigerant standard and come with 6" legs

