

**UNDERCOUNTER
SIDE-MOUNT
REFRIGERATORS
WITH DRAWERS**

VURD93-6

- Equipped with Secure-Temp 1.0™ Technology™
- 3 Year Parts & Labor Warranty Plus an Additional 2 Year Compressor Warranty
- Exclusive 2 Year Warranty on Santoprene Door Gaskets



Secure-Temp 1.0™ is the industry's first and only full service temperature monitoring solution for your kitchen. Secure-Temp 1.0™ is standard on all Victory models and is HACCP compliant & meets NAFEM's data protocol.

There are NO software or monthly monitoring fees.
Optional add on kits are available for additional units.

STANDARD FEATURES

- Secure-Temp 1.0™ Technology
- Expansion Valve Technology
- Full Electronic Control
- High Performance, Balanced, Bottom-Mounted Refrigeration
- Anti-Corrosion Coated Evaporator Coil
- Stainless Steel Front, Sides, Drawers, & Grill
- Interior liner is made of corrosion resistant aluminum
- Cabinet back and bottom galvanized steel
- Environmentally Safe R134A Refrigerant For Freezers
- 2" Thick Foamed-in-Place Polyurethane Insulation
- Santoprene Door Gaskets with Exclusive 2 Year Warranty
- Telescoping drawers slides
- Slides include locking mechanism to prevent drawers from being pulled off of cabinets
- Upper drawers accommodates 6" deep foodservice pans (*pans not included*)
- Lower drawers accommodates 4" deep foodservice pans (*pans not included*)
- 6" Casters Standard, 2 with Brakes
- 10' Cord and Plug (see electrical data for details)

Image Coming Soon

VURD93-6

OPTIONS & ACCESSORIES

- Change Door Swing
- 220/50 Hz, 220/60Hz Voltages
- 3" Overall Height Casters (Set of 4)



Please refer to www.energyguide.gov to view the most up-to-date product listing and performance data

3779 Champion Blvd—Winston-Salem, NC 27105
PH: (888) 845-9800 - Fax: (800) 253-5168
sales@victoryrefrigeration.com www.victoryrefrigeration.com

CABINET CONSTRUCTION

Heavy duty construction includes exterior stainless steel on front, sides, drawers and grille. Cabinet back and bottom are galvanized steel. Interior liner is made of corrosion resistant aluminum. Interior thermometer is standard.

Cabinet is insulated with 2" thick foamed-in-place polyurethane insulation. Sub-top insulated with 1-1/2" foamed-in-place polyurethane insulation. 6" high casters are standard, 2 include brakes. An 8' cord set is provided with 115 volt models.

DRAWER CONSTRUCTION

Drawer frames are constructed of heavy-duty stainless steel and are supported on heavy-duty telescoping drawer slides for maximum support of stored food products. Slides have locking mechanism to prevent from drawers being pulled off of cabinets. Upper pull-out drawers accommodate 6" deep pans. Lower pull-out drawers accommodate two 4" deep pans. Heavy-duty pan divider supports are supplied. Foodservice pans for drawers are not included. Snap-type vinyl magnetic gasket is attached to each drawer for positive seal.

ELECTRONIC CONTROL

REFRIGERATION SYSTEM

Forced air refrigeration systems use expansion valve to meter refrigerant. Automatic electric defrost is standard. Automatic (non-electric) condensate evaporator is provided.

Refrigerators operate at 36°- 38°F

CHARACTERISTICS	VURD93-6
Net Capacity (cu. ft.)	39.8
Width, Overall (in.)	93"
Depth, Overall	33 7/8"
Depth, Door(s) Open 90°	57"
Height Overall	34 1/2"
No. Doors/Drawers	6/-
No. of Shelves	-

ELECTICAL DATA

Condensing Unit Voltage	115/60/1
Total Amperes	8.6

NOTE: Plug style, voltage and full load amps may vary depending on certain options selected such as optional voltages and compressor upgrades.

REFRIGERATION DATA

Condensing Unit Size	1/3 HP
Refrigerant	R-134A

CRATED WEIGHT	442 LBS
---------------	---------

* Remote units use R-404A refrigerant standard and come with 6" legs

