

WORKTOP REFRIGERATORS WITH DRAWERS

VWRD36-2

- Equipped with Secure-Temp 1.0™ Technology™
- 3 Year Parts & Labor Warranty Plus an Additional 2 Year Compressor Warranty
- Exclusive 2 Year Warranty on Santoprene Door Gaskets

VICTORY ULTRASPEC™
FEATURING: **SecureTemp 1.0™**

Secure-Temp 1.0™ is the industry's first and only full service temperature monitoring solution for your kitchen. Secure-Temp 1.0™ is standard on all Victory models and is HACCP compliant & meets NAFEM's data protocol.

There are NO software or monthly monitoring fees.
Optional add on kits are available for additional units.

STANDARD FEATURES

- Secure-Temp 1.0™ Technology
- 3 Year Parts & Labor Warranty Plus an Additional 2 Year Compressor Warranty
- Expansion Valve Technology
- Full Electronic Control
- High Performance, Balanced, Bottom-Mounted Refrigeration
- Anti-Corrosion Coated Evaporator Coil
- Stainless Steel Exterior / Stainless Steel Interior
- Cabinet back and bottom galvanized steel
- Stainless steel 2 1/2" thick worktop with 4" high foamed in place backsplash
- Environmentally Safe R134A Refrigerant For Refrigerators
- 2" Thick Foamed-in-Place Polyurethane Insulation
- Self-Closing Door(s) with 120° Hold Open Feature
- Telescoping Drawer Slides with Locking Mechanism
- Drawers Accommodate 6" or 4" Deep Pans (*pans not included*)
- Santoprene Door Gaskets with Exclusive 2 Year Warranty
- 2 Epoxy Coated Shelves
- 6" Casters Standard, 2 with Brakes
- Cartridge Style Hinges
- 10' Cord and Plug (see electrical data for details)

Image Coming Soon
VWRD63-2

OPTIONS & ACCESSORIES

- Change Door Swing
- 3" Overall Height Casters (Set of 4)
- Extra Shelves
- 220/50Hz, 220/60 Hz Voltages



Please refer to www.energyguide.gov to view the most up-to-date product listing and performance data

3779 Champion Blvd—Winston-Salem, NC 27105

PH: (888) 845-9800 - Fax: (800) 253-5168

sales@victoryrefrigeration.com www.victoryrefrigeration.com

CABINET CONSTRUCTION

Heavy duty construction includes exterior stainless steel on front, sides, door(s) and grille. Cabinet back and bottom are galvanized steel. Interior liner is made of corrosion resistant aluminum. Interior thermometer is standard.

In cabinets with doors and drawers, doors are mounted to face of cabinet on cartridge-style hinges permitting them to self-close under their own weight. Hinges also allow doors to stay open 120° and permit easy door removal for service and cleaning if required. A plug-in type vinyl magnetic gasket is attached to each door for positive seal.

Cabinet insulation is CFC and HCFC-free foamed-in-place polyurethane of two-inch minimum thickness. Units are supplied with 6" high casters. Front casters have wheel locking mechanism.

DRAWER CONSTRUCTION

Drawer frames are constructed of heavy-duty stainless steel. Telescoping design slides make opening drawers smooth and easy. Heavy duty construction ensures maximum support of stored food products. Slides have locking mechanism to prevent drawers from being pulled off of cabinets. For your convenience, drawers accommodate 6" or 4" deep pans. Heavy-duty pan divider supports are supplied. Foodservice pans for drawers are not included. Snap-type vinyl magnetic gasket is attached to each drawer for positive seal.

ELECTRONIC CONTROL

REFRIGERATION SYSTEM

Robust and balanced refrigeration system ensures that food stays fresh for a longer period of time. Optimum air flow inside cabinets helps in keeping uniform temperature within the cabinet. Refrigeration system uses environment friendly R134a refrigerant which is CFC and HCFC- free. Design utilizes automatic condensate removal process.

Refrigerators operate at 36° - 38°F

CHARACTERISTICS	VWRD36-2
DIMENSIONAL DATA	
Width, Overall (in.)	36"
Depth, Overall (inc. Handles)	29 1/4"
Depth, Door(s) Open 90°	55 1/8"
Height Overall (in.)	36"
Capacity Net (cu ft)	17.1
No. Full Doors	-
No. of Shelves	-
No. of Drawers	2

ELECTICAL DATA

Cabinet Voltage	115/60/1
Total Amperes	3.3

NOTE: Plug style, voltage and full load amps may vary depending on certain options selected such as optional voltages and compressor upgrades.

REFRIGERATION DATA

Condensing Unit Size	1/5 HP
Refrigerant	R-134A

CRATED WEIGHT ONE SECTION	210LBS
--------------------------------------	--------

* Remote units use R-404A refrigerant standard and come with 6" legs

