



Project:

Item Number:

Quantity:

CAYENNE® HEAT STRIPS: CORD AND PLUG

MODELS



Note: Must be used with legs - not pictured.

Cayenne® Heat Strip: Cord and Plug unit with lights, shown

DESCRIPTION

The Cayenne® Heat Strip line is intended to be used as a heat source to help maintain food at safe temperatures until served.

FEATURES

- Structurally engineered aluminum heater housing offers maximum strength with minimal weight
- Recessed dovetail channel allows for installation of decorative trim
- Optional Kool-Touch thermoplastic trim drastically reduces fascia temperature for safer operation
- Reflector generates maximum performance for wider heat dispersion and offers larger temperature zone above 140°F (60° C) for safe food holding
- Anodized bright aluminum heat reflector generates more even heat over food display area
- Reflector/heater assembly is field adjustable allowing operator to direct heat pattern for optimum overhead heat
- Sheathed element for dependability and longer life
- Unique element design offers greater heat dispersion for more effective warming
- Two screws allow quick service access to element
- Provided with onboard toggle switch controls
- One year parts and labor warranty. Additional one year warranty on heating element (parts only).
- 6-ft. (182.8 cm) cord and plug
- Lighted units are supplied with the recommended Teflon® coated, shatterproof bulbs. For replacement bulbs, order item 23236.

Length	Wattage ^{1,2}	Item Number	
		Without Lights 120V	With Lights 120V
18" (47.7 cm)	Low	72671019	72671119
	Medium	72672019	72672119
24" (60.9 cm)	Low	72674019	72674119
	Medium	72675019	72675119
30" (76.2 cm)	Low	72677019	72677119
	Medium	72678019	72678119
36" (91.4 cm)	Low	72680019	72680119
	Medium	72681019	72681119
42" (106.6 cm)	Low	72683019	72683119
	Medium	72684019	72684119
48" (121.9 cm)	Low	72686019	72686119
	Medium	72687019	72687119
54" (137.1 cm)	Low	72689019	72689119
	Medium	72690019	72690119
60" (152.4 cm)	Low	72692019	72692119
	Medium	72693019	72693119

- ❶ If ordering C-legs, all low wattage units require 9" (22.8 cm) legs and all medium wattage units require 13" (33.0 cm) legs.
- ❷ Adjustable T-legs are usable with both wattage units.

SELECTING LOW OR MEDIUM WATTAGE

The wattage (low or medium) recommended to keep food at ideal temperatures is determined by height – the distance from the Cayenne® Heat Strip to the surface.

Wattage	Over Non-Combustible Surface		Over Combustible Surface	
	Minimum Height	Maximum Height	Minimum Height	Maximum Height
Low	8" (20.3 cm)	11" (27.9 cm)	11" (27.9 cm)	11" (27.9 cm)
Medium	11" (27.9 cm)	16" (40.6 cm)	13" (33.2 cm)	16" (40.6 cm)

Note: Minimum height is the UL required minimum distance over a combustible or non-combustible surface.

Note: Maximum height is the maximum height to retain food quality under normal conditions.

UL REQUIRED CLEARANCES

Clearance	Non-Combustible Surface	Combustible Surface
Top of strip to surface above (minimum)	1" (2.5 cm)	2" (5.1 cm)
Bottom of strip to surface below	See table above.	
Side of strip to adjacent surface (minimum)	1" (2.5 cm)	5" (12.7 cm)
Setback from front opening on pass thru application: maximum of 8" (20.3 cm)		

Agency Listings



Approvals
Date:



Setting the Standard™


www.vollrathco.com

The Vollrath Company, L.L.C.
 1236 North 18th Street
 Sheboygan, WI 53082-0611
 U.S.A.
 Main Tel: 800.624.2051
 Service Tel: 800.628.0832
 FAX: 800.752.5620

Vollrath of Canada, Co.
 Tel: 800.695.8560
 FAX: 800.752.5620

CAYENNE® HEAT STRIPS: CORD AND PLUG

MOUNTING OPTIONS



T-Leg


C-Leg

Legs

Leg Style	Item Number	For Use With
T-Leg Adjustable 8" to 15" (22.8 to 38.1 cm)	44504	Low or Medium Wattage Units
C-Leg 9" (22.8 cm)	4450609	Low Wattage Units
C-Leg 13" (33.0 cm)	4450613	Medium Wattage Units

ACCESSORIES

Kool-Touch Trim



Item No.	Description
17897xx	Enter unit length at end of part number to add this accessory. One set includes operator and server side coverage. Field trimming required.

Replacement Teflon® Coated Bulbs


Item No.	Description	Case Lot ¹
23236	Teflon® coated, shatterproof bulbs	4

¹ No broken cases.


DIMENSIONS AND RATINGS

All dimensions are in inches (cm). All weights are in Lbs. (kg).

Top View





Front View



Unit	Heater Wattage	Item Number		Amp Draw (120V)		Heat Strip Dimensions				Additional Width of Control Box (D)	Approximate Shipping Weight		Plug
		Without Lights	With Lights	Without Lights	With Lights	Length (A)	Width (C)		Height (B)		Without Lights	With Lights	
							Without Lights	With Lights					
18" (47.7)	Low	300	72671019 / 72671119	2.5	3.2	18" (47.7)	6"	9.125"	2.88"	3"	6.1 (2.7)	9.2 (4.1)	5-15P
	Medium	415	72672019 / 72672119	3.5	4.2						7.2 (3.2)	11 (4.9)	
24" (60.9)	Low	400	72674019 / 72674119	3.3	4.0	24" (60.9)	All Units	All Units	All Units	All Units	8.3 (3.7)	12.9 (5.8)	5-15P
	Medium	550	72675019 / 72675119	4.6	5.3						9.3 (4.1)	14.7 (6.6)	
30" (76.2)	Low	510	72677019 / 72677119	4.3	5.0	30" (76.2)	All Units	All Units	All Units	All Units	10.4 (4.6)	16.4 (7.3)	5-15P
	Medium	690	72678019 / 72678119	5.8	6.5						11.5 (5.1)	18.1 (8.1)	
36" (91.4)	Low	610	72680019 / 72680119	5.1	6.5	36" (91.4)	All Units	All Units	All Units	All Units	12.7 (5.7)	20 (9.0)	5-15P / 5-20P
	Medium	825	72681019 / 72681119	6.9	8.3						13.8 (6.2)	21.9 (9.8)	
42" (106.6)	Low	720	72683019 / 72683119	6.0	7.4	42" (106.6)	All Units	All Units	All Units	All Units	13.8 (6.2)	21.9 (9.8)	5-15P / 5-20P
	Medium	965	72684019 / 72684119	8.0	9.4						15.5 (7.0)	23.6 (10.7)	
48" (121.9)	Low	820	72686019 / 72686119	6.8	8.2	48" (121.9)	All Units	All Units	All Units	All Units	15.5 (7.0)	23.6 (10.7)	5-15P / 5-20P
	Medium	1100	72687019 / 72687119	9.2	10.6						17.2 (6.8)	25.3 (11.5)	
54" (137.1)	Low	925	72689019 / 72689119	7.7	9.8	54" (137.1)	All Units	All Units	All Units	All Units	18.8 (8.5)	26.6 (12.1)	5-15P / 5-20P
	Medium	1240	72690019 / 72690119	10.3	12.4						20.5 (9.3)	28.3 (12.8)	
60" (152.4)	Low	1025	72692019 / 72692119	8.5	10.6	60" (152.4)	All Units	All Units	All Units	All Units	21.9 (9.8)	29.8 (13.5)	5-15P / 5-20P
	Medium	1380	72693019 / 72693119	11.5	13.6						23.6 (10.7)	31.5 (14.3)	

Receptacles



www.vollrathco.com

The Vollrath Company, L.L.C.
 1236 North 18th Street
 Sheboygan, WI 53082-0611
 U.S.A.
 Main Tel: 800.624.2051
 Service Tel: 800.628.0832
 FAX: 800.752.5620

Vollrath of Canada, Co.
 Tel: 800.695.8560
 FAX: 800.752.5620