

Item Number:

Quantity:

CAYENNE® HEAVY-DUTY INDUCTION HOT PLATES



Cayenne® Heavy-Duty Induction Hot Plates

DESCRIPTION

These high-efficiency, heavy-duty, commercial, bench top induction hot plates are designed for use in commercial kitchens. They provide sensitive low-end control for cooking sauces, milks and chocolates as well as fast, high temperature cooking.

The induction hot plates come complete with one or two 30 amp power cords with plugs (see Specifications). The case is made from 18-gauge 304 stainless steel with a vitro ceramic top. The ceramic top is easily cleaned with a mild cleaner.

The induction range is equipped with a variety of safety features including:

- Over-heat protection
- Small-article detection
- Pan auto-detection function
- Empty-pan shut-off

Agency Listings







This device complies with Part 18 FCC Rules.

Due to continued product improvement, please consult www.vollrathco.com for current product specifications.

FEATURES

- ☐ G4 4 IGBT Engine
- Stainless steel framed hobs
- ☐ Firewall control protection
- ☐ Dual commercial, high-flow fans for extra durability
- □ 90% energy efficiency
- ☐ Low 100°F temperature setting for holding applications
- ☐ Same look and operating height as Cayenne[©] charbroilers and griddles

MODELS 912HIMC Dual Hob, Manual Control (US/Canada)

912HIDC Dual Hob, Digital Control (US/Canada) 924HIMC Four Hob, Manual Control (US/Canada) 924HIDC Four Hob, Digital Control (US/Canada)

- ☐ FCC Part 18 approved
- □ Adjustable legs for leveling
- Rubber feet to prevent slipping
- ☐ One year parts and labor warranty

Manual Control Models

- ☐ Knob power control, from 1% to 100%
- Knob guards

Digital Control Models

- ☐ Multi-sensor solid-state controls with digital display
- ☐ Smooth power control from 1% to 100% of output power and temperature control settings in Fahrenheit only
- Push button controls for easy cleaning
- ☐ 1 to 180 minute timer

IMPORTANT

- This appliance is intended for use with induction-ready cookware.
- All models require a minimum ½" clearance between the induction unit and any adjacent hot equipment, such as charbroilers or griddles (do not install flush). Unit draws air from below. Do not install in areas where other equipment can exhaust directly into the induction range.
- □ The maximum intake temperature must not exceed 110°F (43°C). Temperatures are measured in ambient air while all appliances in the kitchen are in operation.

WARRANTY: All models shown come with Vollrath's standard warranty against defects in materials and workmanship. For full warranty details, please refer to the Vollrath Equipment and Smallwares Catalog.

Approvals	Date



CAYENNE® HEAVY-DUTY INDUCTION HOT PLATES


MODELS 912HIMC


912HIMC Dual Hob, Manual Control (US/Canada) 912HIDC Dual Hob, Digital Control (US/Canada) 924HIMC 924HIDC Four Hob, Manual Control (US/Canada)
Four Hob, Digital Control (US/Canada)


DIMENSIONS

Dimensions shown in inches (cm).

Dual Hob 912HIMC / 912HIDC









Front View


Side View

Top View

Four Hob 924HIMC / 924HIDC







Front View

Side View

Top View

ELECTRICAL SPECIFICATIONS

Volts	HZ	Amps	Watts per Hob	Net Weight Ib (kg)	Plug
208-240V AC	50/60	24	2500-2900	47 (21.3)	6-30P
208-240V AC	50/60	24	2500-2900	47 (21.3)	6-30P
208-240V AC	50/60	2 x 24	2500-2900	86 (39)	2 x 6-30P
208-240V AC	50/60	2 x 24	2500-2900	86 (39)	2 x 6-30P
	208-240V AC 208-240V AC 208-240V AC	208-240V AC 50/60 208-240V AC 50/60 208-240V AC 50/60	208-240V AC 50/60 24 208-240V AC 50/60 24 208-240V AC 50/60 2 x 24	Volts HZ Amps Hob 208-240V AC 50/60 24 2500-2900 208-240V AC 50/60 24 2500-2900 208-240V AC 50/60 2 x 24 2500-2900	Volts HZ Amps Hob Ib (kg) 208-240V AC 50/60 24 2500-2900 47 (21.3) 208-240V AC 50/60 24 2500-2900 47 (21.3) 208-240V AC 50/60 2 x 24 2500-2900 86 (39)

Dual hob units feature one power cord and require a single receptacle with a dedicated circuit. Four hob units feature two power cords and require two outlets, each with a dedicated circuit.

Receptacle





The Vollrath Company, L.L.C. 1236 North 18th Street Sheboygan, WI 53081-3201 U.S.A. Customer Service: 800.628.0830

Canada Customer Service: 800.695.8560 Main Fax: 800.752.5620 or 920.459.6573 Technical Services: 800.628.0832 Technical Services Fax: 920.459.5462