RESTAURANT RANGES

VULCAN24" ELECTRIC RESTAURANT RANGE
2 HOT TOPS





SPECIFICATIONS

24" wide electric restaurant range, Vulcan Model No. EV24S-2HT208. Fully MIG welded aluminized steel frame for added durability. Stainless steel front, sides, back riser, plate shelf and 6" adjustable legs. Two 12" x 24" thermostatically controlled hot top sections, 5 KW input. Full width pull out stainless steel crumb tray located beneath the cooking top. Comes with one standard oven. Oven interior measures 20"w x $261/_2$ "d x 14"h. Comes with one oven rack and three rack positions. Oven door is heavy duty with an integrated door hinge / spring mechanism, requiring no adjustments. 5 KW input. Top browning heat control. Thermostat adjusts from 200°F to 500°F. Requires 208 or 240 volt, 1 or 3 phase power supply. All ranges are shipped in 3 phase and are field convertible to single phase.

Exterior Dimensions:

34"d x 24"w x 58"h on 6" adjustable legs

- EV24S-2HT208 2 Hot Tops / Standard Oven / 208V
- EV24S-2HT240 2 Hot Tops / Standard Oven / 240V

STANDARD FEATURES

Item #

- Fully MIG welded aluminized steel frame for added durability
- Stainless steel front, sides, back riser, shelf and legs
- Two 12" x 24" thermostatically controlled hot top sections, 5 KW input
- 5 KW oven with top browning control
- One standard oven, interior measures 20"w x 261/2"d x 14"h
- Full width pull out stainless steel crumb tray
- Thermostat adjusts from 200°F to 500°F
- Cool to the touch control knobs
- One oven rack and three rack positions
- 18" x 26" sheet pans fit front to back
- Requires 208 volt or 240 volt, 1 or 3 phase power supply. (Ranges shipped in 3 phase and are field convertible to single phase)
- One year limited parts and labor warranty

ACCESSORIES (Packaged & Sold Separately)

- Extra oven rack
- Set of four casters (two locking)
- Towel bar
- □ Cutting board
- Condiment rail
- □ Fryer shield



a division of ITW Food Equipment Group LLC

RESTAURANT RANGES

VULCAN


24" ELECTRIC RESTAURANT RANGE 2 HOT TOPS

INSTALLATION INSTRUCTIONS

Clearances from Combustible Construction	<u>Rear</u>	<u>Sides</u>
Range Only	0"	0"

Clearance Note: Electric Ranges are 0 inches sides and 0 inches rear from combustible and non-combustible constructions *except when hot top sections are incorporated.*

Ranges incorporating hot top sections are 0 inches sides and 0 inches rear to non-combustibles and 6 inches sides and 6 inches rear to combustible constructions.



AVAILABLE VOLTAGES - 208 OR 240 VOLT - 1 OR 3 PHASE											
3 PHASE LOADING					NOMINAL AMPS PER LINE WIRE						
MODEL NUMBER	VOLTAGE	TOTAL CONNECTING KW	KW PER PHASE			3 PHASE			1 PHASE		
			X-Y	Y-Z	X-Z	Х	Y	Z			
EV24S-2HT208	208	15.0	5.0	5.0	5.0	41.6	41.6	41.6	72.1		
EV24S-2HT240	240	15.0	5.0	5.0	5.0	36.1	36.1	36.1	62.5		

This appliance is manufactured for commercial use only and is not intended for home use.



P.O. Box 696 Louisville, KY 40201 Toll-free: 1-800-814-2028 Local: 502-778-2791 Quote & Order Fax: 1-800-444-0602