

VC66E SERIES DOUBLE DECK, DEEP DEPTH **ELECTRIC CONVECTION OVENS**

Item # _



Model VC66ED Shown with optional casters







SPECIFICATIONS

Double section, deep depth electric convection oven, Vulcan-Hart Model No. (VC66ED) (VC66EC). Stainless steel front, sides, top and legs. Independently operated stainless steel doors with double pane windows. Non-sag insulation applied to the top, rear, sides, bottom and doors. Porcelain enamel on steel oven interiors measure 29"w x $26\frac{1}{8}$ "d x 20"h. Two interior oven lights per section. Five nickel plated oven racks per section measure 281/4" x 241/2". Eleven position nickel plated rack guides with positive rack stops per section. Each section heated by electric solid sheath elements rated at 12 KW. Furnished with a two speed ½ H.P. oven blowermotor per section. Oven cool switch for rapid cool down. 208 or 240 volt, 60 Hz, 1 or 3 phase.

Exterior Dimensions:

 $40\frac{1}{4}$ "w x $45\frac{1}{8}$ "d (includes motor & door handles) $41\frac{3}{4}$ "d (includes motor only) x 70"h on 8" legs.

NSF listed. UL listed. UL listed to Canadian safety standards.

□ VC66ED Solid state temperature controls adjust from

150° to 500°F. 60 minute timer with audible

alarm.

□ VC66EC Computer controls with digital time and

temperature readouts. 99-hour timer with audible alarm. Roast and Hold cycle.

One hundred programmable menu selections.

Shelf I.D. programming.

STANDARD FEATURES

- Stainless steel front, sides, top and legs.
- Independently operated stainless steel doors with double pane windows.
- 25 total KW.
- $\frac{1}{2}$ H.P. two speed oven blower-motor.
- Moisture vent damper control.
- Oven cool switch for rapid cool down per section.
- Porcelain enamel on steel oven interiors.
- Five nickel plated oven racks with eleven rack positions per section.
- One year limited parts and labor warranty.

O	D.	TI	O	N	C

- ☐ Complete prison package.
- ☐ Security screws only.
- □ Casters.
- ☐ Simultaneous chain driven doors.
- ☐ 480V/60 Hz/1 or 3 phase.
- ☐ Second year extended limited parts and labor warranty.

ACCESSORIES

- ☐ Stainless steel rear motor enclosure.
- □ Extra oven rack(s).
- ☐ Rack hanger(s).
- ☐ Stainless steel drip pan.
- ☐ Down draft flue diverter for direct vent connection.






VC66E SERIES DOUBLE DECK, DEEP DEPTH ELECTRIC CONVECTION OVENS


OPTIONAL VOLTAGES


- ☐ 480 volt, 60 Hz, 3 phase.
- ☐ 220/380 volt, 50 Hz, 1 phase, 3 wire.
- ☐ 220/380 volt, 50 Hz, 3 phase, 4 wire.
- ☐ 240/415 volt, 50 Hz, 3 phase, 4 wire.

CLEARANCES

	Combustible	Non-Combust
Rear	2"	2"
Right Side	4"	4"
Left Side	1"	1"







	NOMINAL AMPS PER LINE WIRE											WEIGHT							
			LOAD		3 PHASE								WITH SKIDS & PACKAGING		WITHOUT SKIDS & PACKAGING				
MODEL	TOTAL CONN.	DHACE			208 VOLT			240 VOLT		480 VOLT		1 PHASE							
NO.	KW	X-Y	Y-Z	X-Z	Х	Υ	Z	Х	Υ	Z	Х	Υ	Z	208V	240V	LBS.	KG	LBS.	KG
VC66E	25	8	8	9	70	66	70	66	58	66	28	30	30	120	104	926	420	810	368



a division of ITW Food Equipment Group LLC

P.O. Box 696 Louisville, KY 40201 Toll-free: 1-800-814-2028 Local: 502-778-2791 Quote & Order Fax: 1-800-444-0602

