HOLDING & TRANSPORT



VPT SERIES PASS THROUGH HOLDING CABINETS



Model VPT15





UL listed. UL listed to Canadian safety standards. Classified by UL to NSF Std. #4.

SPECIFICATIONS

Vulcan Hart Model No. VPT pass through holding cabinets. Blower motor for gentle and even temperature distribution. Complete with 5" heavy duty casters (2 swivel with brakes and 2 rigid). Recessed control panel containing heating indicator light, analog thermometer, and full range thermostat for temperatures up to 190°F (88°C). Cabinet will hold 18" x 26" sheet pans, 12" x 20" steam table pans, or a combination of both on 1½" centers. Complete with universal tray slides adjustable on 1½" centers. Cabinet interior and exterior are both constructed out of 20 gauge stainless steel. Recessed side-mounted handles, magnetic action door latch, and full insulation; 1½" in side walls and 2" in top. Integrated steel frame for maximum strength. Field reversible doors. Complete with top mounted cord and plug: NEMA 5-15 for 120 volts and NEMA 6-15 for 208-240 volts. Lifetime warranty on heating elements.

□ VPT7	Holding & Transport Cabinet
□ VPT13	Holding & Transport Cabinet
□ VPT15	Holding & Transport Cabinet

STANDARD FEATURES

- Pass-Thru Holding Capacity:
 - 18" x 26" sheet pans
 - 12" x 20" pans, or a combination of both on 1½" centers
- Blower motor for gentle and even temperature distribution
- Dutch doors (VPT15 only)
- 5" heavy duty casters (2 swivel with brakes and 2 rigid)
- Recessed side mounted handles
- Recessed control panel
- Heating indicator light
- Analog thermometer
- Full range thermostat for temperatures up to 190°F (88°C)
- Universal tray slides adjustable on 1½" centers. VPT15 & VPT13 ship with 10 pairs of tray slides and VPT7 ships with five pairs.
- Interior and the exterior are both constructed out of 20 gauge stainless steel
- Fully insulated with 1½" in side walls and 2" in top
- Integrated steel frame for maximum strength
- Magnetic action door latch
- Field reversible doors
- Top mounted cord

OPTIONS

- Complete with cord and plug: NEMA 5-15 for 120 volts and NEMA 6-15 for 208-240 volts
- Lifetime warranty on the heating elements

□ Transport latch (field installed)

Additional tray slides

208/240 volt
Humidity pan
Full perimeter bumper
Glass Dutch doors (VPT15 & VPT7 only)
VRH oven racking for VPT7, VPT15
Wire shelves to sit on tray slides
Electronic control with digital display (120V only)





P.O. Box 696 Louisville, KY 40201 Toll-free: 1-800-814-2028 Local: 502-778-2791 Quote & Order Fax: 1-800-444-0602




VPT SERIES PASS THROUGH HOLDING CABINETS


Drawings shown with optional bumper





All Models Top View





VPT15 Front & Side Views

	DIMENSIONS	CAPACITY		ELECTRICAL			SHIPPING WEIGHTS	
MODEL	EXTERIOR	12" x 20" x 2½" PANS	18" x 26" SHEET PANS	VOLTS	WATTS	AMPS	LBS	KG
VPT7	27" W x 34½" D x 40" H	14	7	120	1,000	8.3	198	90
VPT13	27" W x 34½" D x 61" H	26	13	120	1,200	10	270	123
VPT15	27" W x 34½" D x 66½" H	30	15	120	1,200	10	297	135

*per compartment

Optional bumper adds $3\frac{1}{4}$ " to the width and $1\frac{5}{8}$ " to the depth.



a division of ITW Food Equipment Group LLC

P.O. Box 696 Louisville, KY 40201 Toll-free: 1-800-814-2028 Local: 502-778-2791 Quote & Order Fax: 1-800-444-0602