

HEATED HOLDING**VULCAN****VPT SERIES
PASS THROUGH HOLDING CABINETS**

Model VPT15



UL listed. UL listed to Canadian safety standards.
Classified by UL to NSF Std. #4.

SPECIFICATIONS

Vulcan Hart Model No. VPT pass through holding cabinets. Blower motor for gentle and even temperature distribution. Complete with 5" heavy duty casters (2 swivel with brakes and 2 rigid). Recessed control panel containing heating indicator light, analog thermometer, and full range thermostat for temperatures up to 190°F (88°C). Adjustable racking will hold 18" x 26" or 12" x 20" pans or a combination of both on 1½" centers. Lip-load racking will hold 18" x 26" pans on 1½" centers. Shelving will hold a variety of pan sizes. Cabinet interior and exterior are both constructed out of 20 gauge stainless steel. Recessed side-mounted handles, magnetic action door latch, and full insulation; 1½" in side walls and 2" in top. Integrated steel frame for maximum strength. Field reversible doors. Complete with top mounted cord and plug: NEMA 5-15 for 120 volts and NEMA 6-15 for 208-240 volts. Lifetime warranty on heating elements. ENERGY STAR® qualified.

Units with adjustable racking:

- VPT7** (see reverse for capacities)
- VPT13** (see reverse for capacities)
- VPT15** (see reverse for capacities)

Units with lip-load racking:

- VPT7LL** (Fifteen 18" x 26" x 1" sheet pans)
- VPT15LL** (Thirty 18" x 26" x 1" sheet pans)

Units with shelves:

- VPT7SL** (Three Shelves)
- VPT15SL** (Six Shelves)

STANDARD FEATURES

- Pass-Thru Holding Capacity:
 - 18" x 26" sheet pans
 - 12" x 20" pans, or a combination of both on 1½" centers
 - Other pan sizes on shelves
- Blower motor for gentle and even temperature distribution
- Dutch doors (VPT15 only)
- 5" heavy duty casters (2 swivel with brakes and 2 rigid)
- Recessed side mounted handles
- Heating indicator light
- Analog thermometer
- Full range thermostat for temperatures up to 190°F (88°C)
- Universal tray slides adjustable on 1½" centers. VPT15 & VPT13 ship with 10 pairs of tray slides and VPT7 ships with five pairs.
- Interior and the exterior are both constructed out of 20 gauge stainless steel
- Fully insulated with 1½" in side walls and 2" in top
- Integrated steel frame for maximum strength
- Magnetic action door latch
- Field reversible doors
- Top mounted cord
- Complete with cord and plug: NEMA 5-15 for 120 volts and NEMA 6-15 for 208-240 volts
- Lifetime warranty on the heating elements
- ENERGY STAR® qualified

OPTIONS

- 208/240 volt
- Humidity pan
- Full perimeter bumper
- Glass Dutch doors (VPT15 & VPT7 only)
- Wire shelves to sit on tray slides
- Electronic control with digital display (120V only)
- Additional tray slides

VULCAN


a division of ITW Food Equipment Group LLC

P.O. Box 696 ■ Louisville, KY 40201 ■ Toll-free: 1-800-814-2028 ■ Local: 502-778-2791 ■ Quote & Order Fax: 1-800-444-0602




VPT SERIES
PASS THROUGH HOLDING CABINETS


Drawings shown with
optional bumper




All Models Top View



VPT7 Front & Side Views



VPT13 Front & Side Views



VPT15 Front & Side Views

MODEL	DIMENSIONS	CAPACITY		ELECTRICAL			SHIPPING WEIGHTS	
	EXTERIOR	12" x 20" x 2 1/2" PANS	18" x 26" SHEET PANS	VOLTS	WATTS	AMPS	LBS	KG
VPT7	27" W x 34 1/2" D x 40" H	14	7	120	1,000	8.3	198	90
VPT7LL	27" W x 34 1/2" D x 40" H	NA	15	120	1,000	8.3	198	90
VPT7SL	27" W x 34 1/2" D x 40" H	Unit comes with 3 shelves		120	1,000	8.3	198	90
VPT13	27" W x 34 1/2" D x 61" H	26	13	120	1,200	10	270	123
VPT15	27" W x 34 1/2" D x 66 1/2" H	30	15	120	1,200	10	297	135
VPT15LL	27" W x 34 1/2" D x 66 1/2" H	NA	30	120	1,200	10	297	135
VPT15SL	27" W x 34 1/2" D x 66 1/2" H	Unit comes with 6 shelves		120	1,200	10	297	135

*per compartment

Optional bumper adds 3/4" to the width and 1/8" to the depth.



a division of ITW Food Equipment Group LLC

P.O. Box 696 ■ Louisville, KY 40201 ■ Toll-free: 1-800-814-2028 ■ Local: 502-778-2791 ■ Quote & Order Fax: 1-800-444-0602