#### Features & Benefits

- 2 x 2.0 gallon size meets the high volume demands of large sized operations.
- Designed for simplicity, the Handle Operated series brewers save operator time and effort by delivering consistent results from your pre-programmed coffee recipe.
- Twin station configuration provides the flexibility of brewing two different recipes or into two different types of dispensers at the same time!
- Ample 2 gallon capacity is an excellent choice for high volume self service areas such as cafeterias, airports, banquets, casual dining, etc.
- Designed to brew directly into our best-selling LUXUS® L3D series portable dispensers and L3S series servers (sold separately).
- Available in multiple power configurations to efficiently meet your cups-per-hour requirement and keep energy costs at a minimum.

















## **₹** Electrical Configuration

Configuration Code	Heater Configuration	Voltage	Phase	Wires	KW	Electrical Connection	Max Amp Draw	Gallon/Hour
US / CANADA								
C53016	2 x 3.0 kW	120/208-240	1	3+G	4.6-6.1	Hardwired	22.0-25.4	14.0-20.0 <sup>(1)</sup>
C53026	2 x 4.0 kW	120/208-240	1	3+G	6.1-8.1	Hardwired	29.3-33.8	20.0-26.0(1)
C53036 <sup>(2)</sup>	3 x 3.0 kW	120/208-240	3	4+G	7.0-9.1	Hardwired	19.4-22.4	22.0-30.0(1)
C53046 <sup>(2)</sup>	3 x 4.0 kW	120/208-240	3	4+G	9.2-12.1	Hardwired	25.6-29.6	30.0-40.0(1)
C53186	3 x 4.0 kW	440-480	3	3+G	10.3-12.1	Hardwired	13.6-14.8	34.0-40.0(1)
EXPORT								
C53076 <sup>(2)</sup>	3 x 3.0 kW	220-240/380-415	3	4+G	7.8-9.1	Hardwired	11.8-12.9	26.0-30.0(1)
C53086 <sup>(2)</sup>	3 x 4.0 kW	220-240/380-415	3	4+G	10.3-12.1	Hardwired	15.7-17.1	34.0-40.0(1)
C53096 <sup>(2)</sup>	2 x 3.0 kW	220-240	1	2+G	5.1-6.1	Hardwired	23.3-24.4	18.0-20.0(1)
C53106 <sup>(2)</sup>	2 x 4.0 kW	220-240	1	2+G	6.8-8.1	Hardwired	30.9-33.8	24.0-26.0(1)

<sup>(1)</sup> Based on standard factory settings: 4.0 minute brew time; 0% prewet; 200  $^{\circ}$ F water. (2) Requires 3 phase upcharge (Z056).

## Water Specification

Water Inlet 3/8" Male Flare		Minimum Flow Rate  1 <sup>1</sup> / <sub>4</sub> gpm
3/8" Male Flare	20= /5 ncia	1 -/ // anm

# \* Customize Your Brewer

#### **DISPENSERS**

2.0 Gallon LUXUS® Thermal Dispenser(L3D-20) 2.0 Gallon LUXUS® Thermal Server (L3S-20)





L3S-20 Thermal Server



L3D-20 Thermal Dispenser

# **←→** Dimensions

Туре	Height	Width	Depth	Weight
Product	40"	21"	16"	87 lbs
Shipping	38"	23"	24"	100 lbs

### **ACCESSORIES**

Single Serving Station for L3S-15/20 Server	A097
Twin Serving Station for L3S-15/20 Server	A098
Triple Serving Station for L3S-15/20 Server	A099
Quad Serving Station for L3S-15/20 Server	A129
Iced Tea Brew Basket (16" x 6")	B001110G1
OPTIONS	
Orange Dispenser Faucet Replacement Handle	1071.00029.00
Green Dispenser Faucet Replacement Handle	1071.00031.00
Blue Dispenser Faucet Replacement Handle	1071.00032.00
WATER FILTRATION SYSTEM	
In-Line Water Filter (Head / Cartridge / Hose)	A039
Replacement Water Filter Cartridge	A075
PAPER COFFEE FILTERS	
15" x 5 <sup>1</sup> /2" (500/Case)	F001