



CBS-72A with two LUXUS® LBD-6 dispensers shown on counter

CBS-72A

Twin 6.0 Gallon Coffee Brewer High-Volume Brewing

Double brewer and two 6.0 gallon LUXUS® dispensers on a stationary counter. Hassle-free cleaning encourages staff to keep the equipment maintained by featuring full access lids with positive lock slides, quick turn handles and seamless, full drain liners.

Adjustable Programming Parameters:

- Brew Temperature
- Brew Wait
- Bypass Percent
- Drip Delay
- Brew Orifice Size*

*Non-standard brew orifice sizes must be ordered from FETCO®



CTR-72 Counter



LUXUS® LBD-6 dispenser with drip tray

Model	Gallons/Hr	Oz/Hr	8 oz Cups/Hr	12 oz Cups/Hr	16 oz Cups/Hr	20 oz Cups/Hr
CBS-72A	28.2-60.0	3,609-7,680	451-960	300-640	225-480	180-384

Water Specifications

Water Inlet <i>inch</i>	Flow Rate <i>gpm</i>	Water Pressure <i>psig</i>
3/8 Male Flare	3.0	20-75

Measurements

Height <i>inch</i>	Width <i>inch</i>	Depth <i>inch</i>	Empty Weight <i>lbs</i>	Shipping Weight <i>lbs</i>
48 1/8	36	37	420	659

Standard Electrical Configurations

Config. Code	Heater Config.	Voltage	Phase	Wires	KW	Max Amp Draw	Batches/Hour <small>cold water</small>
C72017(1)	3x5.0 KW(3)	120/208	3	4+G	11.6	33.7	4.7
		120/220			13.4	36.7	5.4
		120/240			15.3	38.6	6.2
C72027(2)	3x5.0 KW(3)	120/208	3	4+G	22.8	65.0	6.0
		120/220			26.4	71.0	6.6
		120/240			30.3	74.7	7.2
C72037(1)	3X10 KW(3)	120/208	3	4+G	22.8	65.0	9.3
		120/220	3	4+G	26.4	71.0	10.0
		120/240	3	4+G	30.3	74.7	10.0
C72047(1)	3X10 KW(3)	120/480	3	3+G(4)	30.3	37.9	10.0
C72057(2)	3X10 KW 3)	120/480	3	3+G(4)	60.3	74.7	10.0
*C72107	3X5.0KW(3)	220/240	3	4+G	12.9	33.0	7.2
*C72117	3X10 KW(3)	240/415	3	4+G	25.6	67.3	10.0

Specifications subject to change without notice

(1) With power management

(2) Without power management

(3) On each side

(4) Plus 120V cord and plug

*EXPORT ONLY

