## 3.0 Gallon Twin Station Coffee Brewer WITH IP44 PROTECTION

## Features & Benefits

IP44-62H-30

- 2 x 3.0 gallon size meets the high volume demands of large scale maritime operations.
- IP44 rated coffee brewers are designed and constructed exclusively to withstand harsh conditions found in places such as cruise ship galleys and covered outdoor venues.
- Designed for simplicity, the Handle Operated series brewers save operator time and effort by delivering consistent results from your pre-programmed coffee recipe.
- Twin station configuration provides the flexibility of brewing two different recipes at the same time.
- Brew directly into the ultra durable TPD-30 thermal dispensers (sold separately).
- Available in multiple power configurations to efficiently meet your cups-per-hour requirement and keep energy costs at a minimum.

















# **₹** Electrical Configuration

Configuration Code	Heater Configuration	Voltage	Phase	Wires	KW	Electrical Connection	Max Amp Draw	Gallon/Hour
US / CANADA								
C62206MIP	3 x 3.0 kW	220-240	3	3+G	7.8-9.1	Hardwired	20.5-22.4	9.0-12.0(1)
C62196MIP	3 x 4.0 kW	440-480	3	3+G	10.3-12.1	Hardwired	13.6-14.8	13.5-15.0 <sup>(1)</sup>
C62216MIP	3 x 4.0 kW	380-400	3	3+G	7.7-8.5	Hardwired	11.7-12.3	22.5-24.0(1)
C62186MIP	6 x 4.0 kW	440-480	3	3+G	20.1-24.1	Hardwired	26.8-29.2	25.5-27.0 <sup>(1)</sup>

<sup>(1)</sup> Based on standard factory settings: 4.0 minute brew time; 0% prewet; 200°F water.

## **'\'** Water Specification

Water Inlet	Water Pressure	Minimum Flow Rate
3/8" Male Flare	20-75 psig	2 gpm

# **'** Customize Your Brewer

#### **DISPENSERS**

3.0 Gallon LUXUS® Thermal Dispenser (TPD-30) D012



TPD-30 Thermal Dispenser

## **←** Dimensions

Туре	Height	Width	Depth	Weight
Product	405/8"	35 <sup>1</sup> /2"	227/8"	150 lbs
Shipping	43"	37"	24"	170 lbs

#### **ACCESSORIES**

A069	
A137 B00828003	
1071.00029.00	
1071.00031.00	
1071.00032.00	
A039	
A075	
F004	
F005	